

A mobile lighting tower equipped with a low consumption diesel engine, high-efficiency LED floodlights and a digital controller designed by Generac Mobile® for specific use on lighting towers.



### GENERAC LED

High-efficiency LED floodlights designed by Generac Mobile®.



### GTL01 DIGITAL CONTROLLER

A digital controller specifically designed to manage every function of the lighting tower for ultimate control.

#### V20 L100N

TECHNICAL DATA		
Min. dimensions (mm)	Length x Width x Height	2250 x 1400 x 2436
Max. dimensions (mm)	Length x Width x Height	2640 x 1900 x 8500
Dry weight (kg)		880
Engine model		Yanmar L100N 3000RPM
Avg. sound pressure	dB(A) @ 7m	68
Total running time (h)		91
Lifting system		Hydraulic
Mast rotation (°)		340
Wind speed resistance (km/h)		110
Lamps power (W)		4 x 300
Lamps type		LED
Total lumen (Lm)		153000
Illuminated area (m²)		4200
Alternator	kVA/V/Hz	5/230/50
CEE inlet pug	A/V//Hz	16/230/50
Tank capacity (liters)		100
Liquid containment tank (110%)	√: Yes / ●: No	√

Technical data and pictures in this document may not exactly represent the final product and are not legally binding.